



KÖNIG

BREWING SYSTEMS



THE KÖNIG

DOSER3

INNOVATION FOR TODAY'S BREWERS

konigbrew.com



THE DOSER³

COLD BLOCK DRY
HOPPING/
DOSING SYSTEM



SPECIFICATIONS

- Minimum 10% head space based on volume
- Three sizes 4hl, 8hl, and 11hl for hop charges of 88lbs (40kg), 176lbs (80kg), and 220lbs (100kg) respectively
- Vessel design pressure: 1barg
- Power requirements (typical): 115V, 1Φ, 60Hz, 1.5hp (1.1kW)

STANDARD FEATURES

- Flanged and dished dome top and 90 degree conical bottom
- All 304SS #4 finish outside and inside w/ internal welds ground and polished
- Top mounted glass manway
- Dual CIP spray balls with single-point CIP connection with pressure gauge and CO2 connection
- Dual-blade agitator with off-set top mount gear drive
- Vessel mounted VFD for agitator speed control complete with cord and NEMA 5-15P cord end
- LED light
- Rotatable recirculation port
- Pressure/vacuum relief valve
- Mounted on casters, 2 lockable
- Handle for easy maneuvering

OPTIONS

- Portable transfer pump with two hoses and fittings

BENEFITS

- Sanitary design
- Quick efficient blending
- Low shear
- Low O2 uptake
- Multiple uses

sales@konigbrew.com
604.855.4890